













QTY	Description	Part #	Usage
1	 Filter head 3/8 tube inlet & outlet	QL1	<b>Built On to unit.</b> Manifold head for the water filter. Mount to cabinet wall
1	 Water filter Cartridge	2FC	<b>Built On to unit.</b> Water filter, 1.5gpm, 6,000 gal capacity. Change at least once a year
2	 JG 1/2" mpt to 3/8"	CI321214S	<b>Built On to unit.</b> JG fittings for Shurflo Water Reg inlet and outlet, Attached to Reg
1	 Water Pressure reducer valve, 50 psi	183-150-NF	<b>Built On to unit.</b> Use after the water filter to regulate pressure feeding unit to 50 psi
3	 JG 90 Elbow 3/8" Smooth to 3/8	PP221212W	<b>Built On to unit.</b> Filter head and inlet connections
5	 JG 3/8 Locking Clips	PIC1812R	<b>Built On to unit.</b> Collet locking clip for 3/8" Hose to JG fittings
Parts Shipped separate with unit			
3	 JG 3/8 Locking Clips	PIC1812R	Collet locking clip for 3/8" Hose to JG fittings as needed
1	 JG 3/8 union shut off valve	PPSV041212W	Optional shut off valve for use at unit.
1	 3/8 Tube x 9/26-24 Female Adapter	PSEI6012U9	Optional quick connect fitting adaptor to a 3/8" anglestop
1	 12' Role of 3/8 OD Tube	PE-12-EI-25	Water Inlet and Product hose. Cut in 4 sections to needed lengths

Optional parts

1	 9/26-24 to 3/8 Tube and 9/26-24 mpt	PASVPP6	Angle stop TEE in adaptor. For adding an outlet off the anglestop
1	 Leak Detector alarm and shutoff	CR-LBS10-JG	Leak detector to be installed before filter system includes fittings